

技术参数




技术参数 Smart Marker SM1500

工作频率	83.0, 104.1, 121.6, 134.0, 145.7, 169.8 Hz
材质	High Density PS
尺寸	直径x高度225 x 28 mm
重量	最重300g
ID号码	10位16进制
测深范围	1,5 m (4,9ft)
工作温度	-20 °C ~ +60 °C
使用寿命	大于 50年



技术参数 Marker 2500

工作频率	83.0, 104.1, 121.6, 134.0, 145.7, 169.8 Hz
材质	高密度PS
尺寸	直径x高度225 x 28 mm
重量	最重300g
ID号码	无
测深范围	1,8米, 长信标器 2.5米
工作温度	-20 °C ~ +60 °C
使用寿命	大于 50年


















技术参数 MAR 100-3D

工作频率	83.0, 104.1, 121.6, 134.0, 145.7, 169.8 Hz
材质	PE
尺寸	直径130mm
重量	最大210 g (0,461b)
ID序列号	无
测深	1.2米
工作温度	-20 °C ~ +60 °C
寿命	大于 50年



信标器类型

		信标器颜色		信标探测器类型
83,0 kHz	燃气	黄	  	SML G
101,4 kHz	光纤	橙色	  	SML T
121,6 kHz	雨污管道	绿	  	SML S
145,7 kHz	供水	蓝色	  	SML W
134,0 kHz, 169,8 kHz	电缆	红色	  	SML E